

Fiber Optic Connectors



Features

- Low insertion loss
- High return loss
- Environmentally stable
- Zirconia Ceramic Ferrule

Applications

- Telecommunications Networks
- Local Area Networks
- Data Communication Networks
- Testing instruments
- CATV

Performance Characteristics :

Type	Connector Parts	
Connector	FC/PC, SC/PC, ST/PC	
Insertion Loss (typical)	0.15 (SM)	0.2dB (MM)
Return Loss (typical)	50 – 55db (SM)	
Durability	<0.2dB change after 500 cycles	
Operating temp	-40°C to +75°C	
Storage temp	-55°C to +85°C	

Connector Materials :

Type	Ferrule	Body	Boot
FC Connector (SM, MM)	126um +/-1 Zirconia	Nickel Plated Brass	3 mm. Black Rubber
SC Connector (SM, MM)	126um +/-1 Zirconia	Plastic Housing in Blue	3 mm. Blue Rubber
ST Connector (SM, MM)	126um +/-1 Zirconia	Nickel Plated Brass	3 mm. Black Rubber

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงใด ๆ โดยไม่แจ้งให้ทราบล่วงหน้า รวมทั้งข้อผิดพลาดอันเนื่องมาจากการพิมพ์

We'll provide only the best products and services.

